




Ball bolt
ZC616
Three petals

Ball	Pin	Knob	
		Material	Operating temperature
SUS440C 55HRC	SUS303	Engineering Plastic Orange/black	-30° C ~ 80° C

Spring: SUS piano wire



How to order

1 **2**
ZC616 - 5 - 30
TYPE d L

1											2				unit:mm			
d $\begin{smallmatrix} -0.04 \\ -0.08 \end{smallmatrix}$	E			L							A	B	C	D	Corresponding Hole		Shear force (kN)min.	Weight g
5	5.5	10	15	20	25	30				6				5	+0.06	24	30~32	
6	7	10	15	20	25	30	40	50		7	31.5	38	16	6	-0	35	31~39	
8	9.5			20	25	30	40	50		8				8	+0.08	63	38~47	
10	12				25	30	40	50	60	9				10	-0	100	76~97	
12	14.5					30	40	50	60	70	10	36	43	23		144	57~99	

*L size length can be customized

Copyright © CHENA INDUSTRIAL CO.,LTD ALL RIGHTS RESERVED.

Che Na

FAX 886-2688-3177

info@chena.com.tw




886-22688-3188
886-2688-3881~3

No.21, Guangrong St. Shulin Dist.,
New Taipei City 238 Taiwan (R.O.C.)

Ball bolt
ZC616
Three petals

Ball	Pin	Knob	
		Material	Operating temperature
SUS440C 55HRC	SUS303	Engineering Plastic Orange/black	-30° C ~ 80° C

Spring: SUS piano wire



How to order

ZC616 - 5 - 30

 TYPE d L

1										2				unit:mm			
d	E		L							A	B	C	D	Corresponding Hole	Shear force (KN)min.	Weight g	
5	5.5	10	15	20	25	30				6				5	+0.06	24	30~32
6	7	10	15	20	25	30	40	50		7	31.5	38	16	6	-0	35	31~39
8	9.5			20	25	30	40	50		8				8		63	38~47
10	12				25	30	40	50	60	9				10	+0.08	100	76~97
12	14.5					30	40	50	60	70	10	36	43	23	-0	144	57~99

*L size length can be customized