


4

免鍵軸套
Power Lock

薄肉法蘭型 LP454




材質

表面處理


S45C

-
染黑
無電解鍍

安裝範例



How to order



選擇表面處理

- 無處理..... []
- 染黑..... [B]
- 無電解鍍..... [TN]

單位：mm

d	D	D1	L2	L1	L	支 - M	F KN	TS Nm ²	T Nm	表面壓力 Mpa	質量 (g)
6	14	25	9	21	24	3-M3	4.8	2	14	86	80
8	15	27	12	25	29	3-M4			29	205	100
10	16	28	14	26	30	4-M4	10	5	49	185	120
12	18	32							58	160	140
13	23	38							63	140	
14	23								68	130	150
15	24	45	16	36	42	3-M6	17	127	185	260	
16	24							136	175	250	
17	26	47	18	38	44	4-M6	22	17	180	190	270
18	26								200	160	
20	28	49	25	45	51	6-M6	35	17	220	170	300
22	32	54							250		380
24	34	56							270	120	400
25	34								280		390
28	39	61	25	45	51	35	17	500	150	470	
30	41	62						530		480	

M：公制螺絲 TS：螺絲旋緊轉矩 T,F：在TS下之傳達扭矩及軸向推力

Che Na

(02)2688-3177

info@chena.com.tw

(02)2688-3188
(02)2688-3881~3

新北市樹林區光榮街21號

版權所有 重製必究