




方形鋼片 長型
GF411
夾緊式



本體	圓盤・銷	有頭內六角螺絲
AL 鋁合金 (白色陽極)	不鏽鋼	SCM435 (染黑)
SUS		SUS

How to order

GF411 - 26 - 5-5

TYPE 外徑 d1xd2

選擇本體材質

AL 高強度鋁合金.....空白

SUS.....SUS

版權所有 重製必究

外徑 D	內孔指定 d1-d2		L	e	F	M	G	H	最大扭力 (N·m)		容許軸向位移 (mm)		最高回轉數 (rpm/min)		靜態扭轉 彈簧係數 (N·m/rad)		慣性力矩 (kg·m ²)		質量 g	
	min.	max.							AL	SUS	AL	SUS	AL	SUS	AL	SUS	AL	SUS	AL	SUS
	單位: mm																			
19	3	8	27	9.1	1.8	M2.5	3.3	5.2	1	1.8	±0.18	±0.07	10000		700	790	9.1x10 ⁻⁷	1.6x10 ⁻⁶	14.6	62
26	5	14	35	11.35	2.6	M3	3.9	7.1	1.5	2.2	±0.30	±0.07	5000		1850	2050	3.0x10 ⁻⁶	4.5x10 ⁻⁵	37	95
32	5	15	41	12.25	3.5		3.85	9.5	2	3	±0.36	±0.09	10000		2850	2900	7.6x10 ⁻⁶	1.25x10 ⁻⁵	67	135
34	5	16	45	14.25	4.5	M4	4.85	9.5	3	4.5	±0.36	±0.09	5000		4050	4535	9.0x10 ⁻⁶	1.65x10 ⁻⁵	77	192
39	8	19	50	14.9			4.5	5	11.2	6	9	±0.45	±0.11	10000		9000	10000	3.0x10 ⁻⁵	4.5x10 ⁻⁵	118
44	8	22	64	19.75	5.5	M5	6.4	13.5	25	37	±0.72	±0.18	4700		25000	28000	1.6x10 ⁻⁴	2.1x10 ⁻⁴	318	795
56	10	32											75	23.35	6.3	M6	7.7	15.7	60	90
68	12	38	98	30	8	M8	9.7	22	80	150	±0.25	±0.35	8000		70000	75000	2.5x10 ⁻⁴	3 x10 ⁻⁴	1013	2532
82	17	42											10	10	22	165	245	±0.35	±0.60	4000
94	19	45	102	10	10	M10	10	22	235	340	±1.30	±0.60	8000		60000	65000	1.86x10 ⁻³	2.8x10 ⁻³	1650	3050
104	20	48											12	12	20	350	450	±0.75	±0.75	4000
126	20	55	110	33	12	M12	12	20	350	450	±0.75	±0.75	4000		67500	75600	3.95x10 ⁻³	5.2x10 ⁻³	1980	3850

容許偏角: 1.5°